



Utworzono 21-06-2018

Śruby teowe do mocowań na maszynach DIN 787



Śruby teowe do mocowań na maszynach DIN 787

Materiał :

Stal klasy 8.8

Stal klasy 10.9

Wymiar x szerokość rowka	długość L	długość gwintu b	a	kwadrat e	k
M12 x 14	x 50	35	13.7	22	8
	x 63	45			
	x 80	55			
	x 125	75			
	x 160	100			
	x 200	120			
M16 x 16	x 63	45	15.7	25	9
	x 80	55			
	x 100	65			
	x 125	85			
	x 160	100			
	x 200	125			
	x 250	150			
M16 x 18	x 63	45	17.7	28	10
	x 80	55			
	x 100	65			
	x 125	85			
	x 160	100			
	x 200	125			
	x 250	150			
M20 x 20	x 80	55	19.7	32	12
	x 100	65			
	x 125	85			
	x 160	110			
	x 200	125			
	x 250	150			
	x 315	190			
M20 x 22	x 80	55	21.7	35	14
	x 100	65			
	x 125	85			
	x 160	110			
	x 200	125			
	x 250	150			
	x 315	190			

M24 x 28	x 100	70	27.7	44	18
	x 125	85			
	x 160	110			
	x 200	125			
	x 250	150			
	x 315	190			
	x 400	240			
M30 x 36	x 125	80	35.6	54	22
	x 160	110			
	x 200	135			
	x 250	150			
	x 315	200			
	x 500	300			

www.hexagon.biz.pl