



Utworzono 15-11-2018

Śruby teowe do mocowań na maszynach DIN 787



Śruby teowe do mocowań na maszynach DIN 787

Materiał :

Stal klasy 8.8

Stal klasy 10.9

| Wymiar x szerokość rowka | długość L | długość gwintu b | a | kwadrat e | k |
|--------------------------|-----------|------------------|------|-----------|----|
| M12 x 14 | x 50 | 35 | 13.7 | 22 | 8 |
| | x 63 | 45 | | | |
| | x 80 | 55 | | | |
| | x 125 | 75 | | | |
| | x 160 | 100 | | | |
| | x 200 | 120 | | | |
| M16 x 16 | x 63 | 45 | 15.7 | 25 | 9 |
| | x 80 | 55 | | | |
| | x 100 | 65 | | | |
| | x 125 | 85 | | | |
| | x 160 | 100 | | | |
| | x 200 | 125 | | | |
| | x 250 | 150 | | | |
| M16 x 18 | x 63 | 45 | 17.7 | 28 | 10 |
| | x 80 | 55 | | | |
| | x 100 | 65 | | | |
| | x 125 | 85 | | | |
| | x 160 | 100 | | | |
| | x 200 | 125 | | | |
| | x 250 | 150 | | | |
| M20 x 20 | x 80 | 55 | 19.7 | 32 | 12 |
| | x 100 | 65 | | | |
| | x 125 | 85 | | | |
| | x 160 | 110 | | | |
| | x 200 | 125 | | | |
| | x 250 | 150 | | | |
| | x 315 | 190 | | | |
| M20 x 22 | x 80 | 55 | 21.7 | 35 | 14 |
| | x 100 | 65 | | | |
| | x 125 | 85 | | | |
| | x 160 | 110 | | | |
| | x 200 | 125 | | | |
| | x 250 | 150 | | | |
| | x 315 | 190 | | | |

| | | | | | |
|-----------------|-------|-----|------|----|----|
| M24 x 28 | x 100 | 70 | 27.7 | 44 | 18 |
| | x 125 | 85 | | | |
| | x 160 | 110 | | | |
| | x 200 | 125 | | | |
| | x 250 | 150 | | | |
| | x 315 | 190 | | | |
| | x 400 | 240 | | | |
| M30 x 36 | x 125 | 80 | 35.6 | 54 | 22 |
| | x 160 | 110 | | | |
| | x 200 | 135 | | | |
| | x 250 | 150 | | | |
| | x 315 | 200 | | | |
| | x 500 | 300 | | | |

www.hexagon.biz.pl