



Utworzono 15-11-2018

## Śruby dwustronne o części wkręcanej 1d DIN 938 - PN 82125



### Śruby dwustronne o części wkręcanej 1d DIN 938 - PN 82125

#### Materiał :

Stal klasy 5.8 / 8.8 / 10.9

Stal nierdzewna A2

Stal kwasoodporna A2

| Wymiar             | M 3 | M 4 | M 5 | M 6 | M 7 | M 8 | M 10 | M 12 | M 14 | M 16 | M 18 | M 20 | M 22 | M 24 |
|--------------------|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| <b>b l125</b>      | 12  | 14  | 16  | 18  | 20  | 22  | 26   | 30   | 34   | 38   | 42   | 46   | 50   | 54   |
| <b>b l=130-200</b> | 18  | 20  | 22  | 24  | 26  | 28  | 32   | 36   | 40   | 44   | 48   | 52   | 56   | 60   |
| <b>b l=200</b>     | -   | -   | -   | -   | -   | -   | 45   | 49   | 53   | 57   | 61   | 65   | 69   | 73   |
| <b>e</b>           | 3   | 4   | 5   | 6   | 7   | 8   | 10   | 12   | 14   | 16   | 18   | 20   | 22   | 24   |